

CONTACT CEMENT THINNER/ CLEANER

LIMITED WARRANTY: THE SELLER AND THE MANUFACTURER WILL NOT ACCEPT LIABILITY FOR MORE THAN THE REPLACEMENT OF THIS PRODUCT.

Directions

To restore thickened contact cements, add in small amounts and stir until contact cement regains desired viscosity. An over dilution will cause adhesion problems.

To remove wet contact cement, apply in small amounts and clean.

Do not use on vinyl, linoleum, rubber, acrylic and plastic.

Consult your municipality's regulations for safe disposal of the product.



Warning

1. Always take all necessary precautions in order to avoid contact with eyes and skin. Wear a mask, gloves and safety glasses. Do not breathe vapors.
2. In case of contact with skin, rinse with water and a clean cloth.
3. If in eyes, rinse with water for at least 20 minutes.
4. If inhaled, move the person to fresh air.
5. If swallowed, get immediate medical assistance. Do not induce vomiting.
6. Work in a fresh place away from sunshine and in a well-ventilated area.
7. Keep away from any heat source, flames or sparks.
8. Keep out of reach of children.

Sans frais/ Toll free
Tel: 1 866 772-2948
Fax: 1 866 427-1040
info@superdecapant.com

Distributions J. Des Serres

C.P. 12, Granby, QC J2G 8E2